Journal of Fluids Engineering Editorial Policy Statement on the Control of Numerical Accuracy

Although no standard method for evaluating numerical uncertainty is currently accepted by the CFD community, there are numerous methods and techniques available to the user to accomplish this task. The following is a list of guidelines, enumerating the criteria to be considered for archival publication of computational results in the *Journal of Fluids Engineering*.

- 1. Authors must be precise in describing the numerical method used; this includes an assessment of the formal order of accuracy of the truncation error introduced by individual terms in the governing equations, such as diffusive terms, source terms, and most importantly, the convective terms. It is not enough to state, for example, that the method is based on a "conservative finite-volume formulation," giving then a reference to a general CFD textbook.
- 2. The numerical method used must be at least formally second-order accurate in space (based on a Taylor series expansion) for nodes in the interior of the computational grid. The computational expense of second, third, and higher order methods are more expensive (per grid point) than first order schemes, but the computational efficiency of these higher order methods (accuracy per overall cost) is much greater. And, it has been demonstrated many times that, for first order methods, the effect of numerical diffusion on the solution accuracy is devastating.
- 3. Methods using a blending or switching strategy between first and second order methods (in particular, the well-known "hybrid," "power-law," and related exponential schemes) will be viewed as first-order methods, unless it can be demonstrated that their inherent numerical diffusion does not swamp or replace important modeled physical diffusion terms. A similar policy applies to methods invoking significant amounts of explicitly added artificial viscosity or diffusivity.
- 4. Solutions over a range of significantly different grid resolutions should be presented to demonstrate grid-independent or grid-convergent results. This criterion specifically addresses the use of improved grid resolution to systematically evaluate truncation error and accuracy. The use of error estimates based on methods such as Richardson extrapolation or those techniques now used in adaptive grid methods, may also be used to demonstrate solution accuracy.
- 5. Stopping criteria for iterative calculations need to be precisely explained. Estimates must be given for the corresponding convergence error.
- 6. In time-dependent solutions, temporal accuracy must be demonstrated so that the spurious effects of phase error are shown to be limited. In particular, it should be demonstrated that unphysical oscillations due to numerical dispersion are significantly smaller in amplitude than captured short-wavelength (in time) features of the flow.
- 7. Clear statements defining the methods used to implement boundary and initial conditions must be presented. Typically, the overall accuracy of a simulation is strongly affected by the implementation and order of the boundary conditions. When appropriate, particular attention should be paid to the treatment of inflow and outflow boundary conditions.
- 8. In the presentation of an existing algorithm or code, all pertinent references or other publications must be cited in the paper, thus aiding the reader in evaluating the code and its method without the need to redefine details of the methods in the current paper. However, basic features of the code must be outlined according to Item 1, above.

- 9. Comparison to appropriate analytical or well-established numerical benchmark solutions may be used to demonstrate accuracy for another class of problems. However, in general this does not demonstrate accuracy for another class of problems, especially if any adjustable parameters are involved, as in turbulence modeling.
- 10. Comparison with reliable experimental results is appropriate, provided experimental uncertainty is established. However, "reasonable agreement" with experimental data alone will not be enough to justify a given single-grid calculation, especially if adjustable parameters are involved.

These ten items lay down a set of criteria by which the editors and reviewers of this Journal will judge the archival quality of publications dealing with computational studies for the *Journal of Fluids Engineering*. We recognize that the effort to perform a thorough study of numerical accuracy may be great and that many practical engineering calculations will continue to be performed by first order methods, on a single fixed grid. However, such analyses would not be appropriate for presentation in this archival journal. With the gains in performance of low-end workstations, it is now reasonable to require papers on solutions by CFD to meet these fundamental criteria for archiving of a publication.

With the details of these ten criteria now presented, a shortened statement will appear as follows:

The Journal of Fluids Engineering will not consider any paper reporting the numerical solution of a fluids engineering problem that fails to address the task of systematic truncation error testing and accuracy estimation. Authors should address the following criteria for assessing numerical uncertainty.

- 1. The basic features of the method including formal truncation error of individual terms in the governing numerical equations must be described.
- 2. Methods must be at least second order accurate in space.
- 3. Inherent or explicit artificial viscosity (or diffusivity) must be assessed and minimized.
- 4. Grid independence or convergence must be established.
- 5. When appropriate, iterative convergence must be addressed.
- 6. In transient calculations, phase error must be assessed and minimized.
- 7. The accuracy and implementation of boundary and initial conditions must be fully explained.
- 8. An existing code must be fully cited in easily available references.
- 9. Benchmark solutions may be used for validation for a specific class of problems.
- 10. Reliable experimental results may be used to validate a solution.

References

Celik, I., 1993, "Numerical Uncertainty in Fluid Flow Calculations: Needs for Future Research," ASME JOURNAL OF FLUIDS ENGINEERING, **115**, pp. 194-195.

Roache, P. J., Ghia, K. N., and White, F. M., 1986, "Editorial Policy Statement on the Control of Numerical Accuracy," ASME JOURNAL OF FLUIDS ENGINEERING, **108**, p.2.